

Questionnaire



- Flow rate measurement according to the differential pressure method
- Mass flow restriction using the limiting restriction

Flow rate measurement · When measuring the flow rate in liquids, gases or vapors, the orifice plate assembly generates a differential pressure across the restriction, which is recorded by a connected unit (flow meter or differential pressure transmitter).

SAMSON uses the operating data specified in this questionnaire to size the orifice plate assembly and restriction.







Check the appropriate boxes , cross out any inapplicable dimensions, and specify all pressures as **absolute pressure** (p_{abs}) in bar.

Mass flow restriction · A restriction orifice plate is used to limit the mass flow.

You can fill in, save, print, and e-mail the PDF form.

You can also print out the form, fill it in by hand, and send it back to SAMSON.

Process medium	
Max. flow rate to be measured/restricted	<input type="checkbox"/> kg/h, <input type="checkbox"/> m ³ /h, <input type="checkbox"/> Nm ³ /h
Relating to:	Operating status <input type="checkbox"/> Normal condition at 20 °C and 1 bar <input type="checkbox"/> at 0 °C and 1 bar <input type="checkbox"/>
Pressure upstream of the orifice plate assembly/restriction (operating pressure)	bar
Pressure downstream of the restriction orifice plate	bar
Temperature at the point of measurement (operating temperature)	°C
For liquids	Density under operating conditions <input type="checkbox"/> kg/m ³ Density at 20 °C and 1 bar <input type="checkbox"/> kg/m ³ Viscosity under operating conditions <input type="checkbox"/> cP, cSt
For gases	Density under operating conditions <input type="checkbox"/> kg/m ³ Density at 0 °C and 1013 mbar <input type="checkbox"/> kg/m ³
Actual inside pipe diameter at the point of measurement (not nominal size)	mm
Device arrangement acc. to schematic drawing (see overleaf).	Please enclose a sketch if the system does not correspond to one of the diagrams shown.
Differential pressure at maximum flow rate. Not required if the associated device is delivered by SAMSON.	mbar
Flow rate scale	0 to 100 % <input type="checkbox"/>
Special scale	0 to kg/h <input type="checkbox"/> 0 to m ³ /h <input type="checkbox"/> 0 to <input type="checkbox"/>
Filled in by	Date
Belongs to order no.	
Order	Signature

Device arrangement (schematic) - Observe the mounting and operating instructions of the Media device for each individual case.			
	Liquid measurement	Steam measurement	
Normal installation	 Diagram 1	 Diagram 2	 Diagram 3
Reverse installation	 Diagram 4	 Diagram 5	 Diagram 6

Sketch in case of deviating device arrangement

Print

Send to SAMSON AG

Reset

Specifications subject to change without notice



SAMSON AG · MESS- UND REGELTECHNIK
Weismüllerstraße 3 · 60314 Frankfurt am Main, Germany
Phone: +49 69 4009-0 · Fax: +49 69 4009-1507
samson@samson.de · www.samson.de

T 9500-9 EN

2015-12-15 · English